

Johanson Company: Johanson Dielectrics inc.

Product Release Date: 03 January, 2006

Deprecated P/N: 202S43W223KV4E

Web Page Link:

<https://www.johansondielectrics.com/high-voltage-mlc-capacitors>

Datasheet Date: 05-03-2024

Description: Capacitors High Voltage PME SMD ? 500V, 1812, X7R, 2,000.0V, 0.022 μ F \pm 10%, Ni/Sn (RoHS), 7" Reel Embossed Tape

Size for Capacitors (EIA): 1812

Thickness (Max): 0.110

Life Cycle Stage: Active - Production

End Band (Min):

Schedule B: 8532

End Band (Max):

ECCN: EAR99

Standard Item: 1

RoHS Compliance: Yes, RoHS 10/10

Lead Time Typical (Weeks)*:

*This can vary significantly so it is important to obtain a quotation with lead time for production planning purposes. 10

REACH: 1

Country of Origin: TW

Length (Min): 0.165

Product Family: Capacitors

Length (Max): 0.189

Product Subfamily: Capacitors High Voltage PME SMD ? 500V

Width (Min): 0.115

Capacitance Value: 0.022

Width (Max): 0.135

Cap Unit of Meas: μ F

Packaging: 7" Reel Embossed Tape

Tolerance: \pm 10%

Operating Temp Range: -55°C to +125°C

Voltage: 2000.0

Storage Temp Range (Packaged): -65°C to +125°C

Dielectric Temp Coefficient: X7R

Storage Temp Range (Non Operating): +5°C to +40°C with RH 20% to 70%

Termination: 68

Marking: No Mark